



## **Declaration of Performance**

according to Regulation 305/2011 of the EUROPEAN PARLAMENT and of the COUNCIL laying down harmonized conditions for the marketing of construction products

Identify code	ST/T1/1301	
Тур	Grease separator Lipumax-P-B, D, DM, D	
Use	Grease removal from waste water to protecting drainage systems and surface water	
Manufacturer	ACO Industries Tábor s.r.o., Průmyslová 1158, 39101 Sezimovo Ústí	
Attestation of conformity system	System 4: The manufacturer has discovered the type of product according to the system 4 based of type testing, type calculation tabulated values (or documentation of the product) and carried of factory-owned production control.Document No. 130621LD	
Attestation of conformity system reaction to fire	System 3: The notified agency "test institute Hoch" (NB-Nr. 1508) conducted tests on reaction to fire of the PE components according the system 3, protocol no. 090991.	

The grease separator is built in accordance to the Construction Products Directive 305/2011/EWG.

The following harmonized standards in the current version at the date of issue have been applied:

EN 1825-1:2004	Separator systems for grease – part 1: construction, performance and testing, marking and quality control
EN 1825-2:2002	Separator systems for grease – part 2: selection of nominal size, installation, operation and maintenance
EN 13501-1:2007	Classification of construction products and building their fire behavior – part 1: classification using test data from reaction to fire performance of construction products

Main features	EN 1825-1 Performance		
Reaction to fire	5.2.9	E	
Fluid resistant	5.3.2	pass	
Effectiveness	4, 5.3.1, 5.3.3-5.3.10, 5.5	pass	
Capacity	5.4	pass	
Durability	5.2	pass	

Signed for and on behalf of the manufacturer. Sezimovo Ústí, 27 June 2013

Libor Dočekal (product manager)



## Information accompanying the CE marking



## ACO Industries Tábor s.r.o. Průmyslová 1158 39101 Sezimovo Ústí

11

EN 1825-1:2004

separator systems for grease Lipumax-P-B, D, DM, D with integrated sludge trap

Material: LLDPE Installation parts: PE-HD

## Overview of the CE marked separator systems for grease <u>Typ Lipumax-P-B, D, DM, D</u>

NS	Sludge trap	DN	Ø D (mm)
2	200	100	1320
2	400	100	1320
2/4	400	100	1320
4	800	100	1320
5,5	550	150	1320
5,5	1100	150	1320
7	700	150	1320
8,5	850	150	1320
10	1000	150	1320