



## Declaration of Performance refer to EU BauPVO 305/2011

<b>1 DoP Reference number</b>	ST/G1/5016		
<b>2 Product description</b>	Separator for light liquids Oleopass P		
<b>3 Product specification: (Numbers or Specification of product)</b>	Oleopass P NS x (see following page)		
<b>4 Intended use</b>	Light liquid removal from waste water to protect drainage systems and surface water		
<b>5 Manufacturer</b>	ACO Beton GmbH Mittelriedstraße 25 D-68642 Bürstadt		
<b>6 Authorised representative</b>	Irrelevant		
<b>7 Assessment and verification of constancy of performance</b>	System 3 and System 4		
<b>8 Relevant harmonised standard</b>	DIN EN 858-1:2005 + DIN EN 858-2:2003 + DIN EN 13501-1:2007		
<b>9 First year of CE marking</b>	2012		
<b>10 Notified body</b>	System 3 – Reaction to fire: NB-Nr. 1508		
<b>11 Type test report reference number</b>	Irrelevant		
<b>12 Essential characteristics</b>	<b>Main features</b>	<b>DIN EN 858-1</b>	<b>Performance</b>
	Reaction to fire	6.2.8	E
	Fluid resistant	6.3.2	pass
	Effectiveness	4, 6.3.1, 6.3.3 – 6.3.8, 6.5	pass
	Load-bearing capacity	6.4	pass
	Durability	6.2	pass
<b>13 Specific technical documentation (article 37/38)</b>	Installation manual		
<b>14 Other information</b>	–		

The performance of the product according to No. 2 and 3 is conform to the declared performance in No 12.  
The manufacturer only is responsible for the creation of this declaration of performance according to No. 5.  
Signed for and on behalf of the manufacturer.

Bürstadt, 25th June 2013

Sven Schrothe  
Managing Director





## Declaration of Performance refer to EU BauPVO 305/2011

### Information accompanying the CE marking

ACO Beton GmbH Mittelriedstraße 25 68642 Bürstadt
12
DIN EN 858-1  separator systems for light liquids Oleopass P class I with integrated sludge trap  Material: PE-HD Installation parts: PE-HD

### Overview of the CE marked separator systems for light liquids Type Oleopass P

NS (x)	Sludge trap- volume (l)	Oil storage capacity (l)	Size (mm)
3/15	450	240	1320
3/15	670	240	1320
3/15	950	240	1320
6/30	660	235	1320
6/30	1210	235	1320
8/50	820	260	1320
10/50	1080	260	1320

